## TECHNICAL INFORMATION



No.2407-01656-02E

# Heat-resistant and oxidation-resistant synthetic lubricant



# **♦** Description

S-3103 is is the synthetic oil product.

The performances of this lubricant which are superior heat-resistance, oxidation-resistance and low vapor pressure.

Therefore, it is suitable for the lubricating oil and grease base oil applications in special environments such as high temperature condition.

### ◆ Characteristics

- 1. Withstood for long-term use by superior heat-resistance and oxidation-resistance.
- 2. Withstood for long-term use by extremely small evaporation.
- 3. There is no corrosiveness against metals.

Density	g/cm³ (15 °C)	1.17
Flash point	$^{\circ}\mathrm{C}$	260
Viscosity	$mm^2/s$ (40 °C)	120
Viscosity index		-110
Pour point	$^{\circ}\mathrm{C}$	2.5

#### ♦ How to use

Suitable for the lubricating oil and grease base oil applications in special environments such as high temperature condition and high vacuum condition.

## Storage

Please refer to Safety Data Sheet (SDS)

### Package

100 mL bottle, 500 mL bottle

## **♦** Notes

Importation of this product is not allowed in some countries, or procedures such as application for authorization and quantity reporting are required, which may make it difficult to export this product for replenishment.

Imports that do not comply with the laws and regulations of the destination country may subject the importer to penalties.

Please consult with our sales department before exporting this product or enclosed parts.

株式会社 MORESCO

URL: http://www.moresco.co.jp/ カスタマーセンター(お客様お問合せ専用窓口)

TEL: 06-6262-3385

E-Mail: customercenter@moresco.co.jp

MORESCO Corporation

URL: http://www.moresco.co.jp/

Customer center TEL: +81-6-6262-3385

E-Mail: customercenter@moresco.co.jp